Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

ON Semiconductor®

Silicon NPN Power Transistors

. . . for use in power amplifier and switching circuits, — excellent safe area limits. Complement to PNP 2N5194, 2N5195.

2N5191
2N5192*

*ON Semiconductor Preferred Device

4 AMPERE
POWER TRANSISTORS
SILICON NPN
60–80 VOLTS
40 WATTS



CASE 77–09
TO–225AA TYPE

***MAXIMUM RATINGS**

Rating	Symbol	2N5191	2N5192	Unit
Collector–Emitter Voltage	V_{CEO}	60	80	Vdc
Collector–Base Voltage	V_{CB}	60	80	Vdc
Emitter–Base Voltage	V_{EB}	5.0		Vdc
Collector Current	I_C	4.0		Adc
Base Current	I_B	1.0		Adc
Total Power Dissipation @ T_C = 25°C Derate above 25°C	P_D	40 320		Watts mW/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	–65 to +150		°C

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Case	θ_{JC}	3.12	°C

***ELECTRICAL CHARACTERISTICS** (T_C = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Max	Unit
OFF CHARACTERISTICS					
Collector–Emitter Sustaining Voltage (1) (I_C = 0.1 Adc, I_B = 0)	 2N5191 2N5192	$V_{CEO(sus)}$	 60 80	 — —	Vdc
Collector Cutoff Current (V_{CE} = 60 Vdc, I_B = 0) (V_{CE} = 80 Vdc, I_B = 0)	 2N5191 2N5192	I_{CEO}	 — —	 1.0 1.0	mAdc
Collector Cutoff Current (V_{CE} = 60 Vdc, $V_{EB(off)}$ = 1.5 Vdc) (V_{CE} = 80 Vdc, $V_{EB(off)}$ = 1.5 Vdc) (V_{CE} = 60 Vdc, $V_{EB(off)}$ = 1.5 Vdc, T_C = 125°C) (V_{CE} = 80 Vdc, $V_{EB(off)}$ = 1.5 Vdc, T_C = 125°C)	 2N5191 2N5192 2N5191 2N5192	I_{CEX}	 — — — —	 0.1 0.1 2.0 2.0	mAdc
Collector Cutoff Current (V_{CB} = 60 Vdc, I_E = 0) (V_{CB} = 80 Vdc, I_E = 0)	 2N5191 2N5192	I_{CBO}	 — —	 0.1 0.1	mAdc
Emitter Cutoff Current (V_{BE} = 5.0 Vdc, I_C = 0)		I_{EBO}	—	1.0	mAdc

(1) Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.
*Indicates JEDEC Registered Data.

Preferred devices are ON Semiconductor recommended choices for future use and best overall value.

© Semiconductor Components Industries, LLC, 2002

***ELECTRICAL CHARACTERISTICS — continued** (T_C = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Max	Unit
ON CHARACTERISTICS					
DC Current Gain (2)		h_{FE}			—
(I_C = 1.5 Adc, V_{CE} = 2.0 Vdc)	2N5191		25	100	
	2N5192		20	80	
(I_C = 4.0 Adc, V_{CE} = 2.0 Vdc)	2N5191		10	—	
	2N5192		7.0	—	
Collector–Emitter Saturation Voltage (2)		$V_{CE(sat)}$			Vdc
(I_C = 1.5 Adc, I_B = 0.15 Adc)			—	0.6	
(I_C = 4.0 Adc, I_B = 1.0 Adc)			—	1.4	
Base–Emitter On Voltage (2)		$V_{BE(on)}$	—	1.2	Vdc
(I_C = 1.5 Adc, V_{CE} = 2.0 Vdc)					
DYNAMIC CHARACTERISTICS					
Current–Gain — Bandwidth Product		f_T	2.0	—	MHz
(I_C = 1.0 Adc, V_{CE} = 10 Vdc, f = 1.0 MHz)					

(2) Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.
*Indicates JEDEC Registered Data.



Figure 1. DC Current Gain



Figure 2. Collector Saturation Region



Figure 3. "On" Voltages


*APPLIES FOR $I_C/I_B \leq \frac{h_{FE}\ @\ V_{CE}\ =\ 2.0\ V}{2}$
T_J = −65°C to +150°C
*θ_V for $V_{CE(sat)}$
θ_V for V_{BE}
θ_V, TEMPERATURE COEFFICIENTS (mV/°C)
I_C, COLLECTOR CURRENT (AMP)

Figure 4. Temperature Coefficients



Figure 5. Collector Cut−Off Region


I_C = 10 x I_{CES}
V_{CE} = 30 V
$I_C \approx I_{CES}$
I_C = 2 x I_{CES}
(TYPICAL I_{CES} VALUES
OBTAINED FROM FIGURE 5)
R_{BE}, EXTERNAL BASE−EMITTER RESISTANCE (OHMS)
T_J, JUNCTION TEMPERATURE (°C)

Figure 6. Effects of Base−Emitter Resistance



Figure 7. Switching Time Equivalent Test Circuit



Figure 8. Capacitance



Figure 9. Turn–On Time



Figure 10. Turn–Off Time



Figure 11. Rating and Thermal Data
Active–Region Safe Operating Area

There are two limitations on the power handling ability of a transistor; average junction temperature and second breakdown. Safe operating area curves indicate $I_C - V_{CE}$ limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 11 is based on $T_{J(pk)}$ = 150°C; T_C is variable depending on conditions. Second breakdown pulse limits are valid for duty cycles to 10% provided $T_{J(pk)} \leq$ 150°C. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.



Figure 12. Thermal Response

DESIGN NOTE: USE OF TRANSIENT THERMAL RESISTANCE DATA



Figure A

A train of periodical power pulses can be represented by the model shown in Figure A. Using the model and the device thermal response, the normalized effective transient thermal resistance of Figure 12 was calculated for various duty cycles.

To find $\theta_{JC}(t)$, multiply the value obtained from Figure 12 by the steady state value θ_{JC}.

Example:

The 2N5190 is dissipating 50 watts under the following conditions: t_1 = 0.1 ms, t_p = 0.5 ms. (D = 0.2).

Using Figure 12, at a pulse width of 0.1 ms and D = 0.2, the reading of r(t_1, D) is 0.27.

The peak rise in function temperature is therefore:

$$\Delta T = r(t) \times P_P \times \theta_{JC} = 0.27 \times 50 \times 3.12 = 42.2^{\circ}C$$

PACKAGE DIMENSIONS

TO−225AA
CASE 77−09
ISSUE W



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.425	0.435	10.80	11.04
B	0.295	0.305	7.50	7.74
C	0.095	0.105	2.42	2.66
D	0.020	0.026	0.51	0.66
F	0.115	0.130	2.93	3.30
G	0.094 BSC		2.39 BSC	
H	0.050	0.095	1.27	2.41
J	0.015	0.025	0.39	0.63
K	0.575	0.655	14.61	16.63
M	5° TYP		5° TYP	
Q	0.148	0.158	3.76	4.01
R	0.045	0.065	1.15	1.65
S	0.025	0.035	0.64	0.88
U	0.145	0.155	3.69	3.93
V	0.040	---	1.02	---

STYLE 1:
PIN 1. EMITTER
2. COLLECTOR
3. BASE

Notes

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

Literature Fulfillment:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303–675–2175 or 800–344–3860 Toll Free USA/Canada
Fax: 303–675–2176 or 800–344–3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com

N. American Technical Support: 800–282–9855 Toll Free USA/Canada

JAPAN: ON Semiconductor, Japan Customer Focus Center
4–32–1 Nishi–Gotanda, Shinagawa–ku, Tokyo, Japan 141–0031
Phone: 81–3–5740–2700
Email: r14525@onsemi.com

ON Semiconductor Website: http://onsemi.com

For additional information, please contact your local
Sales Representative.